

Capacitance Microphone (Tables-type) (CM200-TD/TF)

- -Suitable for government enterprise meetings, news broadcast, business speech and other occasions.
- -120 degree rotation, exquisite appearance, height adjustment, convenient and practical.
- -Condenser microphone; perfect for sound display; Long distance for sound acquisition, low noise, low distortion, super cardioid directivity, balanced output.

I. Product model and appearance











Four-Channel Table Style Capacitance Microphone (CM200-TD)

II. Parameters

ТҮРЕ	CM200-TD Dual-Channel CM200-TF Four- Channel	Sensitivity	-30dB
Transducing Mode	Capacitive Type	Output Disturbance	200Ω (Balanced)
Directivity	Supercardioid Single Point	Signal-to-Noise Ratio	>65dB
Consumption Current	2mA	Frequency Response Range	80-20000Hz
Sound Field	Diffusion Field Calibration	Sound Collection Distance	10-60cm
Polar Distance(Referenced)	10-60cm	Connecting Line Length	8m
Color	Black Frosted Baking Paint	Tube Material	Zn based alloy
Power Supply	48V	MIC's Weight (with Tube)	2.9KG (Dual-Chennal) / 3.5KG (Four-Chennal)

III. Characteristics

- With condenser microphone, the frequency response is wide, the sound is thick, clear. Strong pick-up ability, low noise, low distortion, supercardioid directivity, balanced output.
- 2. 120° rotatable mic clip structure, patent for the whole three-dimensional appearance, patent for MIC clip and lifting solid support.

3. It can be adjusted up and down and convenient and practical.

IV. Recommended

It is recommended to use it in combination with GAODIMIC ® UHF Full Sound Range Digital Wireless Audio Transmitter (AT190-SP&SR) to achieve the best engineering layout effect.



IV. Application Scenario

Suitable for high-end government enterprise meetings, news broadcast, business speeches, education lectures and other occasions.

GAODIMIC®

GAODIMIC® is brand of infosvc.biz.

Infosvc information Technologies Service Co., Ltd.

www.infosvc.biz / www.gaodimic.cn